

## Fox SMART LAN

### SMART L 3.0



### Easy Installation

Plug and play installation.



### Strong Signal

Strong LAN signal for maximum range



### IP65 Rated

Suitable for outdoor installation.



### Remote Monitoring

Connect to the FoxCloud.

The Smart L3.0 is an intelligent LAN enabled device allowing you to monitor the status and performance of your Fox PV system via the FoxCloud remote monitoring platform. The Smart L 3.0 is ideal in situations where there is no reliable WiFi or GPRS connection available.

System owners and installers can easily keep up-to-date with performance data in real-time, view historic records and monitor system alerts.

- Stable lan communication
- IP65 protection class
- Vodafone, Tata, Aircel and Airtel compatible
- Clean and compact design
- User-friendly monitoring app
- Plug and play installation
- Monitor your system from anywhere
- 24/7 monitoring



# Fox SMART LAN

## SMART L 3.0

### SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Product Name    | Smart L 3.0                |
| Dimensions [mm] | 100.0 x 49.0 x 28.0        |
| Weight [g]      | 55                         |
| Input Voltage   | DC7-12V                    |
| Power           | 1W(MAX)                    |
| Ethernet Speed  | 10M/100M                   |
| Interface       | RS485                      |
| Parameter       | 9600/8/n/1(default)        |
| Green LED       | Receive Data from Inverter |
| Red LED         | Work status                |
| connector       | USB                        |
| Temperature     | -20°C- +60°C               |
| Humidity        | ≤95%, NO                   |
| Altitude        | ≤4000M                     |
| IP Grade [°C]   | IP65                       |
| Fire rating [%] | UL94V-0                    |
| UV immunity     | F1                         |

